



Catolog

Electromedical products

yuwell

JIANGSU YUYUE MEDICAL EQUIPMENT & SUPPLY CO., LTD

Sales Center Address: Huanyuan East Road No.1, Xuzhuang Software Park, Nanjing,
Jiangsu Province, P.R. China

Tel: 86-25-8713 6530 Fax: 86-25-8713 6530

Manufacturing Address: YunYang Industrial Park, DanYang, Jiangsu Province, P.R. China

Tel: 86-511-8690 0869 86-511-8690 0859 Fax: 86-511-8690 0860

E-mail: yuwellsales@yuyue.com.cn

www.yuwell.com



2015. Yuyue medical, all rights reserved. The "yuwell", yuwell, the yuwell logo and name are trademarked by Jiangsu Yuyue Medical Equipment & Supply Co., Ltd, and may not be distributed, modified, reproduced in whole or in part without the prior. All specifications and product configurations are subject to change without notification.

Suction apparatus

7A-23B Electric suction apparatus

7A-23B type of electric suction apparatus adopts completely plastic panel design, which makes it more fancy and fashionable. The device of intercepting oil for circumfluence can reduce the oil pollution. Easy to carry, low noise, high negative pressure and large flux. It can be widely applied in the surgical operations which need to absorb phlegm, thick liquid etc.

Technical data:
 Power Voltage: AC220V ± 22V, 50Hz ± 1Hz
 Max negative pressure: ≥ 90kPa
 Operation noise: ≤ 65 dB (A)
 Input power: 180VA
 Pumping frequency: ≥ 40L/min
 Reservoir capacity: 2500mL/pc, 2pieces



Oil-free pump

- Clean - no pollution of oil
- Convenient - no need to add oil for maintenance
- Safe - no positive pressure during using

7A-23D Electric suction apparatus

Technical data:
 Power Voltage: AC220V ± 22V, 50Hz ± 1Hz
 Max negative pressure: ≥ 90kPa
 Operation noise: ≤ 65 dB (A)
 Input power: 180VA
 Pumping frequency: ≥ 26L/min
 Reservoir capacity: 2500mL/pc, 2pieces



7B Pedal suction apparatus

Technical data:
 Max negative pressure value: ≥ 0.08MPa
 Negative pressure back-reduction while being closed: ≤ 0.005MPa/10min
 Reservoir capacity: 1000mL
 Pedal pressure: ≤ 245N
 Weight: ≤ 4.5kg

Smaller Lighter Portable

No power are needed to operate this product, making it an ideal equipment for remote areas, village clinic, home care, and situation where no power are present.



7B-1 Manual suction apparatus

Technical data:
 Max vacuum: ≥ 0.04MPa
 Max. flow: ≥ 20L/min
 Suction bottle storage capacity: 200ml
 Weight: 192g
 Refer to 7B type for other functions and parameters.



7C Electrical induced abortion suction apparatus

Designed for induced abortions of pregnancies during the early stage in hospitals. Easily operatable with its full plastic panel design, low noise level and massive flux.

Technical data:
 Input power: 180VA
 Max negative pressure: ≥ 0.08Mpa (1 negative pressure)
 Pumping frequency: ≥ 20L/min
 Reservoir capacity: 500mL/pc, 2pieces
 Refer to 7A-23B type for other functions and parameters.



Portable Phlegm Suction Unit

7E-A Portable Phlegm Suction Unit

7E-A portable phlegm suction unit is a product with oil-free lubrication pump based on extensive research and development of both domestic and international product design. It is specially designed to absorb thick liquid such as blood, phlegm etc. It can be used as aspirator in operation room, hospital, or simply a health care product used at home.

Features:

High negative pressure, large flux, low noise. It is a brand new mechanism design with suction bottle built in and square negative pressure meter crust. This design not only can reduce the made noise level but also makes it more precise.

It adopts advanced overflow-protection design, which can prevent pus and mucus from leaking into the machine.

Compact, lightweight, and portable, suitable for emergency and outside use.

Technical data:

Input power: 90VA
 Max negative pressure value: $\geq 0.075\text{MPa}$
 Pumping rate: $\geq 17\text{L/min}$
 Operation noise: $\leq 65\text{dB (A)}$
 Reservoir volume: 1000mL, 1piece
 Working system: short running



7E-C Portable Phlegm Suction Unit

Designed with streamline shape, portable, cool down system, circular negative pressure meter, half hidden type liquid storage bottle and a detachable power line.

Technical data:

Input power: 90VA
 Max negative pressure value: $\geq 0.075\text{MPa}$
 Pumping rate: $\geq 15\text{L/min}$
 Noise: $\leq 65\text{dB (A)}$
 Reservoir volume: 1000mL, 1piece
 Working system: short running



7E-B Portable Phlegm Suction Unit

Suction for children

Adopting oil-free lubrication piston pump, square negative pressure dial. Small size, low noise, more portable, built-in bottle, it is suitable for children use.

Pumping rate: $\geq 15\text{L/min}$

Refer to 7E-A type for other functions and parameters.

7E-D Portable Phlegm Suction Unit

This product can function under any of the three power source: alternating current and direct current and batteries. It is most used in situation where power source are lacking, such as on vehicles or in the outdoors.

Technical data:

DC Power supply: 12V
 Input power: 44VA
 Pumping rate: $\geq 15\text{L/min}$
 Working system: Continuous operation with intermittent loading, maximum continuous working time is 30 minutes, continuity rate: 50%
 Refer to 7E-A type for other functions and parameters.



7E-G Portable Phlegm Suction Unit

This product can function under any of the three power source: alternating current and direct current and batteries. It is most used in situation where power source are lacking, such as on vehicles or in the outdoors.

Technical data:

DC Power supply: 12V
 Working system: Continuous operation with intermittent loading, maximum continuous working time is 30 minutes, continuity rate: 50%

- Power supply of the suction apparatus and suction unit:
 AC120V $\pm 10\%$ AC220V $\pm 10\%$ AC230V $\pm 10\%$ 50Hz 60Hz